

# The `latex-lab-table` package

## Changes related to the tagging of tables

Frank & Ulrike, L<sup>A</sup>T<sub>E</sub>X Project\*

v0.85r 2025-05-01

### Abstract

The following code implements a first draft for the tagging of tables. It still has a large number of limitations and restrictions!

## Contents

<b>1</b>	<b>Documentation</b>	<b>2</b>
1.1	Loading . . . . .	2
1.2	Untagged and presentation tables . . . . .	3
1.3	Header rows and columns . . . . .	3
1.4	Spanning of cells . . . . .	3
<b>2</b>	<b>Limitations</b>	<b>4</b>
<b>3</b>	<b>Introduction</b>	<b>5</b>
<b>4</b>	<b>Technical details and problems</b>	<b>5</b>
4.1	TODOs . . . . .	5
<b>5</b>	<b>Implementation</b>	<b>5</b>
5.1	Variables . . . . .	5
5.2	Tagging support sockets . . . . .	6
5.3	Environments . . . . .	15
5.4	Interfaces to tagging . . . . .	15
5.4.1	Tagging helper commands . . . . .	15
5.4.2	Disabling/enabling . . . . .	15
5.4.3	Header support . . . . .	17
5.5	Multirow support . . . . .	19
5.6	Misc stuff . . . . .	21
5.7	longtable . . . . .	22

---

\*Initial implementation done by Frank Mittelbach

# 1 Documentation

In  $\text{\LaTeX}$  the word `table` is used as the name of the float environment that can contain a data table<sup>1</sup> along with a caption and some additional text. The environments for actual data tables have various names like `tabular`, `tabular*`, `tabularx` and `longtable`—the last should not be used inside a float and supports its own caption command.

In this documentation “table” always means such data tables and not the float environment.

Tagging of tables is on one side doesn’t look very difficult: one only has to surround rows and cells by TR and TH or TD structures. But there are difficulties:

- One is that over the years various packages related to tables have been written that all change some of the internals. Inserting the tagging commands and testing all the variants and various nestings is not trivial.
- The other difficulty is that most of the existing environments to create tables do not know the concept of headers as a semantic structures.
- Headers are only produced through visual formatting, e.g., by making them bold or by underlying some color. But accessible tables need headers (and the PDF/UA standards requires them) and this means that additional syntax to declare headers (when they can’t be guessed) must be developed. This is still an area for research.

Right now, this module therefore does implement only some basic support for the tagging of tables. A list of the known limitations is shown below.

## 1.1 Loading

The module is not loaded automatically (i.e., not yet integrated into any `phase-XX`) and by itself it doesn’t activate tagging. For experimenting with table tagging it is therefore best to load it in combination with `phase-III` in `\DocumentMetadata`, i.e.:

```
\DocumentMetadata{testphase={phase-III,table}}
```

It will then automatically tag all table environments it already supports with the exception of tables in the header and footer of the page (where tagging is disabled). Such tables can be nested.

Inside cells the automatic tagging of paragraphs is disabled with the exception of p/m/b-type cells.

Rows do not need to contain a full number of `&`, missing cells are automatically added with an empty TD-structure.

You should not insert meaningful text with `!\{...\}` or `@{...\}` or `\noalign` between the rows or columns of the table. With `pdflatex` such text will be unmarked, with `lualatex` it will be marked as artifact. Either case means that it will be currently ignored in the structure.<sup>2</sup>

As mentioned below the `colortbl` doesn’t work fully with the tagging, but when it does, colors inside the table are currently ignored. If such a color has a semantic meaning (like “important value”) this meaning will be lost.

---

<sup>1</sup>But it does not really have to, you can put other material into such environments.

<sup>2</sup>While it is theoretically possible to collect such text and move it into a structure it would require manual markup from the author to clarify where this text belongs too.

## 1.2 Untagged and presentation tables

If a table should not be tagged as table, for example because it is merely used as a layout to ensure that the content is properly aligned or because it is a not yet (fully) supported table structure, the tagging can be disabled with `\tagpdfsetup{table/tagging=false}` or changed with `\tagpdfsetup{table/tagging=presentation}` or `\tagpdfsetup{table/tagging=div}`

<sup>3</sup> The first option disables the table tagging code and the content of the tabular is then treated more or less like running text. This works ok for simple tables using only hmode-cells (l/c/r) with normal text content, but fails if the table uses vmode-cells (p/m/b). In such cases the second option works better: it keeps the tagging code active, but adds an ARIA-role as attribute to indicate that this is a presentation table. When deriving to html this gives the best result as it keeps the layout. The last option changes the tag names and creates simply a number of DIV structures. Both options also (re)set the `table/header-rows` and `table/header-columns` keys to empty.

To reset to the normal tagging in the current group (e.g. inside a presentation table) one can use `\tagpdfsetup{table/tagging=true}` (and if needed reenale the headers).

## 1.3 Header rows and columns

There is some basic support<sup>4</sup> for headers. With<sup>5</sup>

```
\tagpdfsetup{table/header-rows={\list of row numbers}}
\tagpdfsetup{table/header-columns={\list of column numbers}}
```

you can declare which (absolute) row and column numbers should be tagged as header rows and header columns. It applies to all tables until it is changed to a different list of row or columns numbers or undone by setting the keys to `\empty`. A row or column number can be negative, then the counting starts from the end of the table. In a `longtable` the code will currently use the `\endhead` or `\endfirsthead` rows as header if one of these commands has been used and in that case the code ignores a `table/header-rows` setting.

## 1.4 Spanning of cells

`\multicolumn` is supported out of the box and will create a structure with a suitable `ColSpan` attribute<sup>6</sup>

For cells spanning rows some preliminary support exists<sup>7</sup>: If you add

```
\tagpdfsetup{table/multirow={\number of rows}}
```

to a cell the code will add the suitable `RowSpan` attribute and suppress the tagging of affected cells in the following rows. This will also work if the current cell is a `\multicolumn`, then the cell will span both rows and columns. It is the duty of the author to ensure that all cells below and covered by a `RowSpan` are empty! The code neither checks that nor does it tries to suppress content.

Feedback and problems with the code can be reported at <https://github.com/latex3/tagging-project> either in form of explicit issues or as a “discussion topic”, whatever works best.

<sup>3</sup>The key has been renamed. The old name ‘table-tagging’ still works but is deprecated. The value `presentation` refers to the ARIA role “presentation”.

<sup>4</sup>This is not meant to be the final interface, though.

<sup>5</sup>The old key name `table-header-rows` still works but is deprecated.

<sup>6</sup>The code uses actually an attribute *class*. The validator PAC doesn’t handle this correctly currently and complains about a missing attribute.

<sup>7</sup>The interface is bound to change!

## 2 Limitations

- The code loads the `array` package and so does not work without it (that is not really a limitation, but can affect existing tables).
- It supports only a restricted number of tables types. Currently `tabular`, `tabular*`, `tabularx`, and `longtable`.
- the `array` environment is assumed to be part of math and tagging as a table is disabled for it.
- Row spans can only be added manually (the `multirow` package is untested).
- The `colortbl` package breaks tagging if there are nested tables.
- The `tabularray` package use a completely different method to create tables and will not be supported by this code.
- The `nicematrix` package is currently incompatible.
- Most other packages related to tables in L<sup>A</sup>T<sub>E</sub>X are not fully tested, that includes packages that change rules like `booktabs`, `hhline`, `arydshln`, `hvdashln`. Some problems have been resolved, either in the packages or through a firstaid which can be loaded the `testphase=firstaid`.
- `longtable` currently only works with `lualatex`. With other engines it breaks as its output routine clashes with the code which closes open MC-chunks at pagebreaks and if this is resolved there will probably be problems with the head and foot boxes (but this can't be tested currently).
- Not every table should be tagged as a Table structure, often they are only used as layout help, e.g. to align authors in a title pages. In such uses the tagging of the table must be deactivated with `\tagpdfsetup{table/tagging=false}` or changed with `\tagpdfsetup{table/tagging=presentation}` or `\tagpdfsetup{table/tagging=div}`.
- Only simple header rows and columns are currently supported. Complex headers with subheaders will be handled later as that needs some syntax changes. Tables with more than one header row or column are probably not pdf/UA as the headers array in the cells is missing.
- A `longtable` `\caption` is currently simply formatted as a multicolumn and not tagged as a `Caption` structure.
- The `caption` package will quite probably break the `longtable` caption.
- The setup for `longtable` requires lots of patches to internal `longtable` commands and so can easily break if other packages try to patch `longtable` too.
- The `longtable` environment supports footnotes in p-type columns, but it hasn't been tested yet if this works also with the tagging code.
- Vertical boxes (`\parbox`, `minipage`, ...) inside cells can be problematic.
- The code is quite noisy and fills the log with lots of messages.<sup>8</sup>

---

<sup>8</sup>Helpful for us at this stage.

### 3 Introduction

### 4 Technical details and problems

The implementation has to take care of various details.

#### 4.1 TODOs

- Test `array-006-longtable.lvt` and `array-007-longtable.lvt` have errors with pdfTeX (para tagging)
- Instead of before/after hooks we should add sockets directly into the code.
- Debugging code and messages must be improved.
- Cells need an `Headers` array.
- Row spans should be supported (but perhaps need syntax support)
- Longtable captions should be properly supported.
- More packages must be tested.

### 5 Implementation

```
1 <@@=tbl>
2 <*package>

3 \ProvidesExplPackage {latex-lab-testphase-table} {\ltblabtbldate} {\ltblabtblversion}
4   {Code related to the tagging of tables}
```

This builds on `array` so we load it by default:

```
5 \RequirePackage{array}
```

#### 5.1 Variables

This is for the celltag, e.g. TD or TH:

```
6 \tl_new:N \l__tbl_celltag_tl
7 \tl_set:Nn \l__tbl_celltag_tl {TD}
8 \tl_new:N \l__tbl_pcelltag_tl
9 \tl_set:Nn \l__tbl_pcelltag_tl {TD}
```

For the rowtag, probably always TR:

```
10 \tl_new:N \l__tbl_rowtag_tl
11 \tl_set:Nn \l__tbl_rowtag_tl {TR}
```

For the tabletag, probably always Table:

```
12 \tl_new:N \l__tbl_tabletag_tl
13 \tl_set:Nn \l__tbl_tabletag_tl {Table}
```

And here cell and row attributes:

```
14 \tl_new:N \l__tbl_cellattribute_tl
15 \tl_set:Nn \l__tbl_cellattribute_tl {}
16 \tl_new:N \l__tbl_rowattribute_tl
17 \tl_set:Nn \l__tbl_rowattribute_tl {}
```

Variable to store cell info like which cell must be skipped when tagging multirows.

```
18 \prop_new:N\g__tbl_untagged_cells_prop
19 \prop_new:N\l__tbl_saved_untagged_cells_prop
```

Temp variables

```
20 \clist_new:N \l__tbl_tmpa_clist
21 \tl_new:N \l__tbl_tmpa_tl
22 \str_new:N \l__tbl_tmpa_str
```

(End of definition for \l\_\_tbl\_celltag\_tl \l\_\_tbl\_pcelltag\_tl and others.)

## 5.2 Tagging support sockets

This are the standard plugs for tagging of cells and rows.

The following two sockets are defined in lttagging, but we check for their existence until the release 11/2024.

```
23 \socket_if_exist:nF {tagsupport/tbl/init/celldata}
24 {
25   \NewTaggingSocket{tbl/init/celldata}{0}
26   \NewTaggingSocket{tbl/restore/celldata}{0}
27 }
```

**default (plug)** This socket is used inside \tbl\_init\_cell\_data\_for\_table for the case that this a nested table in a cell.

```
28 \NewTaggingSocketPlug{tbl/init/celldata}{default}
29 {
30   \prop_set_eq:NN\l__tbl_saved_untagged_cells_prop \g__tbl_untagged_cells_prop
31   \prop_gclear:N \g__tbl_untagged_cells_prop
32 }
33 \AssignTaggingSocketPlug{tbl/init/celldata}{default}
```

**default (plug)** This socket is used inside \tbl\_restore\_outer\_cell\_data: and restores values when a nested table is ended.

```
34 \NewTaggingSocketPlug{tbl/restore/celldata}{default}
35 {
36   \prop_gset_eq:NN\g__tbl_untagged_cells_prop \l__tbl_saved_untagged_cells_prop
37 }
38 \AssignTaggingSocketPlug{tbl/restore/celldata}{default}
```

**TD (plug)**

```
39 \NewTaggingSocketPlug{tbl/cell/begin}{TD}
40 {
```

Next line was previously outside of the plug, so if we want to execute it always even if the noop plug is in force this needs a different solution.

```
41   \__tbl_show_curr_cell_data:
```

We test if the cell should be tagged at all.

```
42   \__tbl_if_tag_cell:nnT {\g__tbl_row_int } {\g__tbl_col_int }
43   {
```

this sets row headers

```

44     \clist_if_in:NVT \l__tbl_header_columns_clist\g__tbl_col_int
45     {
46         \tl_set:Nn \l__tbl_celltag_tl {TH}
47         \tl_set:Ne \l__tbl_cellattribute_tl {\l__tbl_cellattribute_tl,TH-row}
48     }

```

Here we handle negative value for row headers:

```

49     \tl_set:Ne \l__tbl_tmpa_tl
50     {\int_eval:n { \g__tbl_col_int - 1 - \g__tbl_table_cols_tl }}
51     \clist_if_in:NoT \l__tbl_header_columns_clist { \l__tbl_tmpa_tl }
52     {
53         \tl_set:Nn \l__tbl_celltag_tl {TH}
54         \tl_set:Ne \l__tbl_cellattribute_tl {\l__tbl_cellattribute_tl,TH-row}
55     }
56     \tag_struct_begin:n
57     {
58         tag           =\l__tbl_celltag_tl,
59         attribute-class ={\l__tbl_cellattribute_tl}
60     }
61     \seq_gput_right:Ne \g__tbl_struct_cur_seq { \tag_get:n {struct_num} }

```

we store the cells of multicolumns as negative number. This allow to skip them or to use them as needed.

```

62     \int_step_inline:nn { \g__tbl_span_tl - 1 }
63     {
64         \seq_gput_right:Ne \g__tbl_struct_cur_seq { -\tag_get:n {struct_num} }
65     }
66     \tag_mc_begin:n{ }
67 }
68 }

```

TD (*plug*)

```

69 \NewTaggingSocketPlug{tbl/cell/end}{TD}
70 {
71     \__tbl_if_tag_cell:nnT {\g__tbl_row_int } { \g__tbl_col_int }
72     {
73         \tag_mc_end:
74         \tag_struct_end:
75     }
76 }

```

In p-columns we need a slightly different plug which reactivates the paragraph tagging.

TDpbox (*plug*)

```

77 \NewTaggingSocketPlug{tbl/pcell/begin}{TDpbox}
78 {
79     \__tbl_show_curr_cell_data:
80     \__tbl_if_tag_cell:nnT {\g__tbl_row_int } { \g__tbl_col_int }
81     {
82         \clist_if_in:NVT \l__tbl_header_columns_clist\g__tbl_col_int
83         {
84             \tl_set:Nn \l__tbl_celltag_tl {TH}

```

```

85         \tl_set:Nc \l__tbl_cellattribute_tl {\l__tbl_cellattribute_tl,TH-row}
86     }
87     \tag_struct_begin:n
88     {
89         tag              =\l__tbl_pcelltag_tl,
90         attribute-class ={\l__tbl_cellattribute_tl}
91     }
92     \seq_gput_right:Nc \g__tbl_struct_cur_seq { \tag_get:n {struct_num} }
93     \int_step_inline:nn { \g__tbl_span_tl - 1 }
94     {
95         \seq_gput_right:Nc \g__tbl_struct_cur_seq { -\tag_get:n {struct_num} }
96     }
97     \tagpdfparaOn
98     \tl_set:Nn \l__tag_para_main_tag_tl {Div}
99 }
100 }

```

TDpbox (*plug*)

```

101 \NewTaggingSocketPlug{tbl/pcell/end}{TDpbox}
102 {
103     \__tbl_if_tag_cell:nnT {\g__tbl_row_int } { \g__tbl_col_int }
104     {
105         \tag_struct_end:
106         \legacy_if:nT {@endpe}{\par}
107         \mode_if_vertical:T{ \tagpdfparaOff }
108     }
109 }

```

TR (*plug*)

```

110 \NewTaggingSocketPlug{tbl/row/begin}{TR}
111 {
112     \seq_gclear:N \g__tbl_struct_cur_seq
113     \tag_struct_begin:n
114     {
115         tag              =\l__tbl_rowtag_tl,
116         attribute-class=\l__tbl_rowattribute_tl
117     }
118     \seq_gput_right:Nc \g__tbl_struct_rows_seq { \tag_get:n {struct_num} }
119 }

```

TR (*plug*)

```

120 \NewTaggingSocketPlug{tbl/row/end}{TR}
121 {
122     \tag_if_active:T
123     {
124         \__tbl_add_missing_cells:
125         \seq_gput_right:Nc \g__tbl_struct_cells_seq
126         {
127             \seq_use:Nn \g__tbl_struct_cur_seq {,}
128         }
129         \int_compare:nNnTF { \g__tbl_row_int } =
130             { \seq_count:N \g__tbl_struct_cells_seq }
131         {
132             \__tbl_trace:n

```



```

133         {==>~
134             structure~stored~for~row~\int_use:N\g__tbl_row_int :~
135             \seq_use:Nn \g__tbl_struct_cur_seq {,}
136         }
137     }
138     { \ERRORtbl/row } % should not happen ...
139 \tag_struct_end:
140 }
141 }

```

And the plugs for the table as whole. The code can be different for normal tables which can also be used inline and nested and “vmode” tables like longtable.

`\l__tag_block_flattened_level_int` Count the levels of nested blockenvs starting with the first that is “flattened”. The counter is defined in ltagging.dtx, but until the next release 11/24 we set it up here too so that we can use it in the following socket

```

142 \int_if_exist:NF \l__tag_block_flattened_level_int
143 {
144     \int_new:N \l__tag_block_flattened_level_int
145 }

```

(End of definition for `\l__tag_block_flattened_level_int`.)

**Table (plug)** Inside a TD or TR Part is not allowed as child. For structures that restore paragraph settings we therefore need a special plug that adjust the settings. Currently we set the para main tag to Div. This leads to double Div-structures but flattening the paragraph doesn’t work, it errors if there is a list inside.

```

146 \NewTaggingSocketPlug{para/restore}{Table}
147 {
148     \tl_set:Nn \l__tag_para_main_tag_tl {Div}
149     \tl_set_eq:NN \l__tag_para_tag_tl\l__tag_para_tag_default_tl
150     \bool_set_true:N \l__tag_para_bool
151     \bool_set_false:N \l__tag_para_flattened_bool
152     \int_zero:N \l__tag_block_flattened_level_int
153 }

```

**Table (plug)** Inside a table we currently only disable paratagging. We assume that these sockets are called in a group, so there is no need to reenale paratagging.

```

154 \NewTaggingSocketPlug{tbl/init}{Table}
155 {
156     \bool_set_false:N \l__tag_para_bool
157     \AssignTaggingSocketPlug{para/restore}{Table}

```

We also initialize the structure data variables at this point.

```

158     \__tbl_init_struct_data:
159 }

```

**Table (plug)** This plug will fine tune the structure.

```

160 \NewTaggingSocketPlug{tbl/finalize}{Table}
161 {
162     \__tbl_set_header_rows:

```

Similarly, we restore the outer values of the structure data when we leave the table.

```

163     \__tbl_restore_struct_data:
164 }

```

**Table (plug)** This plug will initialize the structure in longtable.

```

165 \NewTaggingSocketPlug{tbl/longtable/init}{Table}
166 {
167   \seq_gclear:N\g__tbl_struct_rows_seq
168   \seq_gclear:N\g__tbl_struct_cells_seq
169   \seq_gclear:N\g__tbl_struct_cur_seq
170   \seq_gclear:N\g__tbl_LT@firsthead_rows_seq
171   \seq_gclear:N\g__tbl_LT@head_rows_seq
172   \seq_gclear:N\g__tbl_LT@lastfoot_rows_seq
173   \seq_gclear:N\g__tbl_LT@foot_rows_seq
174 }

```

**Table (plug)** This plug will fine tune the structure in longtable.

```

175 \NewTaggingSocketPlug{tbl/longtable/finalize}{Table}
176 {

```

If neither `\endhead` nor `\endfirsthead` has been used we use the standard header command:

```

177   \bool_lazy_and:nnTF
178     { \seq_if_empty_p:N \g__tbl_LT@head_rows_seq }
179     { \seq_if_empty_p:N \g__tbl_LT@firsthead_rows_seq }
180     { __tbl_set_header_rows: }

```

Otherwise, if firsthead has not been used we use head. For this we simple retrieve the row numbers and then call the header command.

```

181   {
182     \seq_if_empty:NTF \g__tbl_LT@firsthead_rows_seq
183     {
184       \clist_set:Nc \l__tbl_header_rows_clist
185         { \seq_use:Nn \g__tbl_LT@head_rows_seq {,} }
186       \__tbl_set_header_rows:
187     }

```

In the other case we use firsthead.

```

188   {
189     \clist_set:Nc \l__tbl_header_rows_clist
190       { \seq_use:Nn \g__tbl_LT@firsthead_rows_seq {,} }
191     \__tbl_set_header_rows:

```

Additionally we have to remove the head to avoid duplication. The one option here is to remove the rows from the kid sequence of the table (which will lead to orphaned structure elements), the other to make them artifact. For now we use the first option for pdf 1.7 and the second for pdf 2.0.

```

192     \pdf_version_compare:NnTF < {2.0}
193     {
194       \seq_map_inline:Nn \g__tbl_LT@head_rows_seq
195       {
196         \seq_gset_item:cnn
197           {g__tag_struct_kids_ \g__tbl_struct_table_t1 _seq}
198           { ##1 }
199       }

```

Not sure if needed, but if needed we can remove also the P tag. This is currently disabled as it produce warnings. TODO: This needs also a tagpdf command which takes care of debug code.

```

200         \tl_set:Nc \l__tbl_tmpa_tl
201         { \seq_item:Nn \g__tbl_struct_rows_seq {##1} }
202     \prop_if_exist:cT
203     { g__tag_struct_ \l__tbl_tmpa_tl _prop }
204     {
205         %\prop_gremove:cn {g__tag_struct_ \l__tbl_tmpa_tl _prop} {P}
206     }
207 }
208 }
209 {
210     \seq_map_inline:Nn \g__tbl_LT@head_rows_seq
211     {
212         \tl_set:Nc \l__tbl_tmpa_tl
213         { \seq_item:Nn \g__tbl_struct_rows_seq {##1} }
214         \prop_if_exist:cT
215         { g__tag_struct_ \l__tbl_tmpa_tl _prop }
216         {
217             \__tag_struct_prop_gput:onn { \l__tbl_tmpa_tl } {S}{/Artifact}
218         }
219     }
220 }
221 }
222 }

```

The foot is handled similar, the difference is that we have to move it to the end one of them is not empty, but do nothing if they aren't there.

```

223     \bool_lazy_and:nnF
224     { \seq_if_empty_p:N \g__tbl_LT@foot_rows_seq }
225     { \seq_if_empty_p:N \g__tbl_LT@lastfoot_rows_seq }
226     {

```

If lastfoot is empty move foot to the end.

```

227         \seq_if_empty:NTF \g__tbl_LT@lastfoot_rows_seq
228         {
229             \seq_map_inline:Nn \g__tbl_LT@foot_rows_seq
230             {
231                 \tl_set:Nc \l__tbl_tmpa_tl
232                 {
233                     \seq_item:cn
234                     {g__tag_struct_kids_ \g__tbl_struct_table_tl _seq}
235                     {##1}
236                 }
237                 \seq_gset_item:cnn
238                 {g__tag_struct_kids_ \g__tbl_struct_table_tl _seq}
239                 { ##1 }
240                 {}
241                 \seq_gput_right:cV
242                 {g__tag_struct_kids_ \g__tbl_struct_table_tl _seq}
243                 \l__tbl_tmpa_tl
244             }
245         }

```

If lastfoot is not empty we move that.

```

246         {
247             \seq_map_inline:Nn \g__tbl_LT@lastfoot_rows_seq

```

```

248     {
249       \tl_set:Nc \l__tbl_tmpa_tl
250       {
251         \seq_item:cn
252         {g__tag_struct_kids_ \g__tbl_struct_table_tl _seq}
253         {##1}
254       }
255       \seq_gset_item:cnn
256       {g__tag_struct_kids_ \g__tbl_struct_table_tl _seq}
257       { ##1 }
258       {}
259       \seq_gput_right:cV
260       {g__tag_struct_kids_ \g__tbl_struct_table_tl _seq}
261       \l__tbl_tmpa_tl
262     }

```

and we hide foot

```

263     \pdf_version_compare:NnTF < {2.0}
264     {
265       \seq_map_inline:Nn \g__tbl_LT@foot_rows_seq
266       {
267         \seq_gset_item:cnn
268         {g__tag_struct_kids_ \g__tbl_struct_table_tl _seq}
269         { ##1 }
270         {}

```

Not sure if needed, but if needed we can remove also the P tag. This is currently disabled as it produce warnings. TODO: This needs also a tagpdf command which takes care of debug code.

```

271       \tl_set:Nc \l__tbl_tmpa_tl
272       { \seq_item:Nn\g__tbl_struct_rows_seq {##1} }
273       \prop_if_exist:cT
274       { g__tag_struct_ \l__tbl_tmpa_tl _prop }
275       {
276         %\prop_gremove:cn {g__tag_struct_ \l__tbl_tmpa_tl _prop} {P}
277       }
278     }
279   }
280   {
281     \seq_map_inline:Nn \g__tbl_LT@foot_rows_seq
282     {
283       \tl_set:Nc \l__tbl_tmpa_tl
284       { \seq_item:Nn\g__tbl_struct_rows_seq {##1} }
285       \prop_if_exist:cT
286       { g__tag_struct_ \l__tbl_tmpa_tl _prop }
287       {
288         \__tag_struct_prop_gput:onn {\l__tbl_tmpa_tl} {S}{/Artifact}
289       }
290     }
291   }
292 }
293 }
294 }

```

Table (*plug*) We must avoid that the reuse of the header foot box leads to duplicated content, thus reset attribute of the box:

```

295 \NewTaggingSocketPlug{tbl/longtable/head}{Table}
296 {
297   \tagmcbegin{artifact}
298   \tag_mc_reset_box:N\LT@head
299   \tagmcend
300 }

```

Table (*plug*)

```

301 \NewTaggingSocketPlug{tbl/longtable/foot}{Table}
302 {
303   \tagmcbegin{artifact}
304   \tag_mc_reset_box:N \LT@foot
305   \tagmcend
306 }

```

Table (*plug*)

```

307 \NewTaggingSocketPlug{tbl/hmode/begin}{Table}
308 {
309   \tag_mc_end_push:

```

Close the P-chunk. This assumes that para-tagging is active. For nested tables that is not necessarily true, so we test for it.

```

310   \bool_lazy_and:nnT
311     { \bool_if_exist_p:N \l__tag_para_bool } { \l__tag_para_bool }
312     { \tag_struct_end:n { text } }
313   \tag_struct_begin:n {tag=\l__tbl_tabletag_tl}
314   \tl_gset:Ne \g__tbl_struct_table_tl { \tag_get:n {struct_num} }
315 }

```

LayoutTable (*plug*) This plug is meant for presentation tables, it sets the ARIA role.

```

316 \NewTaggingSocketPlug{tbl/hmode/begin}{LayoutTable}
317 {
318   \tag_mc_end_push:

```

Close the P-chunk. This assumes that para-tagging is active. For nested tables that is not necessarily true, so we test for it.

```

319   \bool_lazy_and:nnT
320     { \bool_if_exist_p:N \l__tag_para_bool } { \l__tag_para_bool }
321     { \tag_struct_end:n { text } }
322   \tag_struct_begin:n {tag=\l__tbl_tabletag_tl,attribute-class=ARIA-role=presentation}
323   \tl_gset:Ne \g__tbl_struct_table_tl { \tag_get:n {struct_num} }
324 }

```

Table (*plug*)

```

325 \NewTaggingSocketPlug{tbl/hmode/end}{Table}
326 {
327   \tag_struct_end:

```

reopen the P-chunk. This assumes that para-tagging is active. For nested tables that is not necessarily true, so we test for it.

```

328   \bool_lazy_and:nnT
329     { \bool_if_exist_p:N \l__tag_para_bool } { \l__tag_para_bool }

```

```

330     { \tag_struct_begin:n { tag=\l__tag_para_tag_tl } }
331     \tag_mc_begin_pop:n{}
332 }

```

Table (*plug*)

```

333 \NewTaggingSocketPlug{tbl/vmode/begin}{Table}
334 {
335     \tag_struct_begin:n {tag=\l__tbl_tabletag_tl}
336     \tl_gset:Ne \g__tbl_struct_table_tl { \tag_get:n {struct_num} }
337 }

```

Table (*plug*)

```

338 \NewTaggingSocketPlug{tbl/vmode/begin}{LayoutTable}
339 {
340     \tag_struct_begin:n {tag=\l__tbl_tabletag_tl,attribute-class=ARIA-role-presentation}
341     \tl_gset:Ne \g__tbl_struct_table_tl { \tag_get:n {struct_num} }
342 }

```

Table (*plug*)

```

343 \NewTaggingSocketPlug{tbl/vmode/end}{Table}
344 {
345     \tag_struct_end:
346     \par
347 }

```

**code (*plug*)** This socket takes a number, checks if is larger than one, checks if the colspan attribute already exists (we can't predefine an arbitrary number), and updates \l\_\_tbl\_cellattribute\_tl.

```

348 \NewTaggingSocketPlug{tbl/colspan}{code}
349 {
350     \int_compare:nNnT {#1}>{1}
351     {
352         \prop_get:NeNF \g__tag_attr_entries_prop
353         {colspan-\int_eval:n{#1}}
354         \l__tbl_tmpa_tl
355         {
356             \__tag_attr_new_entry:ee
357             {colspan-\int_eval:n{#1}}
358             {/0 /Table /ColSpan-\int_eval:n{#1}}
359         }
360         \tl_set:Ne \l__tbl_cellattribute_tl
361         {\l__tbl_cellattribute_tl,colspan-\int_eval:n{#1}}
362     }
363 }

```

**code (*plug*)** The sockets will be in ltagging.dtx, but that may only happen in the next main release, so for now we test if they are in the format and if not define them now.

```

364 \str_if_exist:cF { l__socket_tagsupport/tbl/leaders/end_plug_str }
365 {
366     \NewTaggingSocket{tbl/leaders/begin}{0}
367     \NewTaggingSocket{tbl/leaders/end}{0}
368 }

```

```

369 \NewTaggingSocketPlug{tbl/leaders/begin}{code}
370 { \tag_mc_begin:n{artifact} }
371 \NewTaggingSocketPlug{tbl/leaders/end}{code}
372 { \tag_mc_end: }

```

### 5.3 Environments

Currently we support only tabular, tabular\*, tabularx and longtable (and possibly environments build directly on top of them).

The `array` environment is math. So we disable table tagging for now. We use the command hook to catch also cases where `\array` is used directly in other environments like matrix environments. Perhaps table tagging should be disable for math generally, but then we have to handle text insertions.

```

373 \AddToHook{cmd/array/before}{\__tag_tbl_disable:}

```

### 5.4 Interfaces to tagging

#### 5.4.1 Tagging helper commands

#### 5.4.2 Disabling/enabling

For now we have only the option true/false but this will probably be extended to allow different setups like first row header etc.

`\__tag_tbl_disable:`

```

374 \cs_new_protected:Npn \__tag_tbl_disable:
375 {
376   \AssignTaggingSocketPlug{tbl/cell/begin}{noop}
377   \AssignTaggingSocketPlug{tbl/cell/end}{noop}
378   \AssignTaggingSocketPlug{tbl/pcell/begin}{noop}
379   \AssignTaggingSocketPlug{tbl/pcell/end}{noop}
380   \AssignTaggingSocketPlug{tbl/row/begin}{noop}
381   \AssignTaggingSocketPlug{tbl/row/end}{noop}
382   \AssignTaggingSocketPlug{tbl/init}{noop}
383   \AssignTaggingSocketPlug{tbl/finalize}{noop}
384   \AssignTaggingSocketPlug{tbl/longtable/init}{noop}
385   \AssignTaggingSocketPlug{tbl/longtable/head}{noop}
386   \AssignTaggingSocketPlug{tbl/longtable/foot}{noop}
387   \AssignTaggingSocketPlug{tbl/longtable/finalize}{noop}
388   \AssignTaggingSocketPlug{tbl/hmode/begin}{noop}
389   \AssignTaggingSocketPlug{tbl/hmode/end}{noop}
390   \AssignTaggingSocketPlug{tbl/vmode/begin}{noop}
391   \AssignTaggingSocketPlug{tbl/vmode/end}{noop}
392   \AssignTaggingSocketPlug{tbl/colspan}{noop}
393   \AssignTaggingSocketPlug{tbl/leaders/begin}{noop}
394   \AssignTaggingSocketPlug{tbl/leaders/end}{noop}
395 }

```

*(End of definition for \\_\_tag\_tbl\_disable:.)*

`\__tag_tbl_enable:`

```

396 \cs_new_protected:Npn \__tag_tbl_enable:
397 {
398   \AssignTaggingSocketPlug{tbl/cell/begin}{TD}

```

```

399 \AssignTaggingSocketPlug{tbl/cell/end}{TD}
400 \AssignTaggingSocketPlug{tbl/pcell/begin}{TDpbox}
401 \AssignTaggingSocketPlug{tbl/pcell/end}{TDpbox}
402 \AssignTaggingSocketPlug{tbl/row/begin}{TR}
403 \AssignTaggingSocketPlug{tbl/row/end}{TR}
404 \AssignTaggingSocketPlug{tbl/init}{Table}
405 \AssignTaggingSocketPlug{tbl/finalize}{Table}
406 \AssignTaggingSocketPlug{tbl/longtable/head}{Table}
407 \AssignTaggingSocketPlug{tbl/longtable/foot}{Table}
408 \AssignTaggingSocketPlug{tbl/longtable/init}{Table}
409 \AssignTaggingSocketPlug{tbl/longtable/finalize}{Table}
410 \AssignTaggingSocketPlug{tbl/hmode/begin}{Table}
411 \AssignTaggingSocketPlug{tbl/hmode/end}{Table}
412 \AssignTaggingSocketPlug{tbl/vmode/begin}{Table}
413 \AssignTaggingSocketPlug{tbl/vmode/end}{Table}
414 \AssignTaggingSocketPlug{tbl/colspan}{code}
415 \AssignTaggingSocketPlug{tbl/leaders/begin}{code}
416 \AssignTaggingSocketPlug{tbl/leaders/end}{code}
417 }

```

(End of definition for `\_tag\_tbl\_enable:`.)

```

\__tbl_init_tagnames_default: These commands are used to switch the tagnames.
\__tbl_init_tagnames_div:
418 \cs_new_protected:Npn\__tbl_init_tagnames_default:
419 {
420   \tl_set:Nn\l__tbl_rowtag_tl {TR}
421   \tl_set:Nn\l__tbl_pcelltag_tl {TD}
422   \tl_set:Nn\l__tbl_celltag_tl {TD}
423   \tl_set:Nn\l__tbl_tabletag_tl {Table}
424 }
425
426 \cs_new_protected:Npn\__tbl_init_tagnames_div:
427 {
428   \tl_set:Nn\l__tbl_rowtag_tl {NonStruct}
429   \tl_set:Nn\l__tbl_pcelltag_tl {NonStruct}
430   \tl_set:Nn\l__tbl_celltag_tl {text}
431   \tl_set:Nn\l__tbl_tabletag_tl {Div}
432 }

```

(End of definition for `\_tbl\_init\_tagnames\_default:` and `\_tbl\_init\_tagnames\_div:`.)

```

433 % See tagpdfsetup-keys.md in tagpdf/doc for the naming scheme.
434 \keys_define:nn { __tag / setup }
435 {
436   table/tagging .choices:nn = { true, on }
437   {
438     \__tag_tbl_enable:
439     \__tbl_init_tagnames_default:
440   },
441   table/tagging .choices:nn = { false, off }
442   { \__tag_tbl_disable: },
443   table/tagging .choice:,
444   table/tagging / presentation .code:n =
445   {
446     \__tag_tbl_enable:

```



```

447     \tbl_init_tagnames_default:
448     \AssignTaggingSocketPlug{tbl/hmode/begin}{LayoutTable}
449     \AssignTaggingSocketPlug{tbl/vmode/begin}{LayoutTable}
450     \clist_clear:N \l__tbl_header_rows_clist
451     \clist_clear:N \l__tbl_header_columns_clist
452   },
453   table/tagging / div .code:n =
454   {
455     \__tag_tbl_enable:
456     \tbl_init_tagnames_div:
457     \AssignTaggingSocketPlug{tbl/hmode/begin}{LayoutTable}
458     \AssignTaggingSocketPlug{tbl/vmode/begin}{LayoutTable}
459     \clist_clear:N \l__tbl_header_rows_clist
460     \clist_clear:N \l__tbl_header_columns_clist
461   },
462   table/tagging .default:n = true,
463   table/tagging .initial:n = true
464 }

```

This are the old key names kept for now for compatibility. They will got at some time.

```

465 \keys_define:nn { __tag / setup }
466 {
467   table-tagging .meta:n = {table/tagging={#1}}
468 }

```

### 5.4.3 Header support

Accessible table must have header cells declaring the meaning of the data in a row or column. To allow a data cell to find it header cell(s) a number of things must be done:

- every cell meant as a header should use the tag **TH**.
- header cells should have a **Scope** attribute with the value **Column**, **Row** or **Both**. This is not needed in the first row or column of a table.
- For more complex cases both TD and TH cell can contain a **Headers** attribute, that is an array of IDs of TH cell.

For now we support only header rows.

At first we define attributes for the three standard cases: We delay to begin document as we can't know if tagpdf is already loaded.

```

469 \AddToHook{begindocument}
470 {
471   \tag_if_active:T
472   {
473     \tagpdfsetup
474     {
475       role/new-attribute =
476       {TH-col}{/O /Table /Scope /Column},
477       role/new-attribute =
478       {TH-row}{/O /Table /Scope /Row},
479       role/new-attribute =
480       {TH-both}{/O /Table /Scope /Both},
481       role/new-attribute =

```

```

482         {ARIA-role-presentation}{/O /ARIA-1.1/role (presentation)}
483     }

```

And we put all three into the class map (perhaps the next tagpdf should do that directly with role/new-attribute):

```

484     \seq_gput_left:Ne\g__tag_attr_class_used_seq
485     {\pdf_name_from_unicode_e:n{TH-col}}
486     \seq_gput_left:Ne\g__tag_attr_class_used_seq
487     {\pdf_name_from_unicode_e:n{TH-row}}
488     \seq_gput_left:Ne\g__tag_attr_class_used_seq
489     {\pdf_name_from_unicode_e:n{TH-both}}
490 }
491 }
492

```

---

```

\l__tbl_header_rows_clist
\l__tbl_header_columns_clist

```

---

This holds the numbers of the header rows and columns. Negative numbers are possible and count from the last column backwards.

```

493 \clist_new:N \l__tbl_header_rows_clist
494 \clist_new:N \l__tbl_header_columns_clist

```

`\__tbl_set_header_rows:`

```

495 \cs_new_protected:Npn \__tbl_set_header_rows:
496 {
497     \clist_map_inline:Nn \l__tbl_header_rows_clist
498     {
499         \clist_set:Ne\l__tbl_tmpa_clist
500         {
501             \seq_item:Nn \g__tbl_struct_cells_seq {##1}
502         }
503         \clist_map_inline:Nn \l__tbl_tmpa_clist
504         {

```

We can have negative numbers in the list from the multicolumn.

```

505         \prop_if_exist:cT { g__tag_struct_####1_prop }
506         {
507             \__tag_struct_prop_gput:nnn{ ####1 }{S}{/TH}

```

This sets the scope class. If the header has already a row attribute we replace by TH-both.

```

508         \prop_get:cnNTF
509         { g__tag_struct_####1_prop }
510         { C }
511         \l__tbl_tmpa_tl
512         {
513             \str_set:Ne \l__tbl_tmpa_str {\l__tbl_tmpa_tl}
514             \str_remove_once:Nn \l__tbl_tmpa_str {}
515             \str_remove_once:Nn \l__tbl_tmpa_str {}
516             \str_if_in:NnTF\l__tbl_tmpa_str{/TH-row}
517             {
518                 \str_replace_once:Nnn \l__tbl_tmpa_str {/TH-row}{/TH-both}
519                 \__tag_struct_prop_gput:nne{ ####1 }{C}{[\l__tbl_tmpa_str]}
520             }

```

```

521         {
522         \__tag_struct_prop_gput:nne{ #####1 }{C}{[/TH-col~\l__tbl_tmpa_str]}
523         }
524     }
525     {\__tag_struct_prop_gput:nnn{ #####1 }{C}{/TH-col}}
526 }
527 }
528 }
529 }

```

(End of definition for `\__tbl_set_header_rows:`)

And some key support: (See `tagpdfsetup-keys.md` for the naming scheme.)

```

530 \keys_define:nn { __tag / setup }
531 {
532     table/header-rows .clist_set:N = \l__tbl_header_rows_clist,
533     table/header-columns .clist_set:N = \l__tbl_header_columns_clist,

```

obsolete older name:

```

534     table-header-rows .meta:n = {table/header-rows={#1}}
535 }

```

## 5.5 Multirow support

`\__tbl_multirow:n` This command makes the current cell into a multirow cell: it creates, if needed, an `RowSpan`-attribute, adds it to the attributes of the cell structure, and marks all following cells spanned by the multirow as cells that should not be tagged. The argument is the number of spanned row (including the current row).

```

536 \cs_if_exist:NT \__tag_struct_prop_gput:nnn
537 {
538     \cs_generate_variant:Nn \__tag_struct_prop_gput:nnn {one}
539 }
540 \cs_new_protected:Npn \__tbl_multirow:n #1
541 {

```

Create an attribute if needed:

```

542     \prop_get:NcNF \g__tag_attr_entries_prop
543         {rowspan-\int_eval:n{#1}}
544     \l__tbl_tmpa_tl
545     {
546         \__tag_attr_new_entry:ee
547         {rowspan-\int_eval:n{#1}}
548         {/O /Table /RowSpan~\int_eval:n{#1}}
549     }

```

ensure that the attribute is marked as used:

```

550     \seq_gput_left:Nc\g__tag_attr_class_used_seq
551         {\pdf_name_from_unicode_e:n{rowspan-\int_eval:n{#1}}}

```

Get the structure number of the current cell

```

552     \seq_get_right:NN\g__tbl_struct_cur_seq \l__tbl_tmpb_tl

```

If we are in a multicolumn the number can be negative and this must be changed

```

553     \tl_set:Nc \l__tbl_tmpb_tl { \int_abs:n{\l__tbl_tmpb_tl} }

```

no we must update an existing attribute. TODO: simplify this ... (see also colspan handling).

```

554 \prop_get:cnNTF
555 { g__tag_struct_\l__tbl_tmpb_tl _prop }
556 { C }
557 \l__tbl_tmpa_tl
558 {
559   \tl_remove_once:Nn \l__tbl_tmpa_tl {[}
560   \tl_remove_once:Nn \l__tbl_tmpa_tl {]}
561   \__tag_struct_prop_gput:one{ \l__tbl_tmpb_tl }
562   {C}
563   {[ /rowspan-\int_eval:n{#1}~\l__tbl_tmpa_tl]}
564 }
565 {
566   \__tag_struct_prop_gput:one{ \l__tbl_tmpb_tl }
567   {C}
568   {[ /rowspan-\int_eval:n{#1}]}
569 }

```

Now mark the spanned cells that should be ignored.

```

570 \__tbl_gset_untagged_row_cells:nn {#1-1}{\g__tbl_span_tl}
571 }

```

(End of definition for \\_\_tbl\_multirow:n.)

```

572 \keys_define:nn{ __tag / setup }
573 { table/multirow .code:n = {\__tbl_multirow:n {#1} }
574   ,table/multirow .default:n = 1
575 }

```

\\_\_tbl\_gset\_untagged\_row\_cells:nn

This command stores the row and column numbers of the cells in the following row(s) that should not be tagged as they are a part of a rowspan.

```

576 \cs_new_protected:Npn \__tbl_gset_untagged_row_cells:nn #1 #2
577 % #1 number of rows, #2 number of columns
578 {
579   \int_step_inline:nn {#1}
580   {
581     \int_step_inline:nn {#2}
582     {
583       \prop_gput:Nee \g__tbl_untagged_cells_prop
584       {
585         \int_eval:n {\g__tbl_row_int + ##1},
586         \int_eval:n {\g__tbl_col_int + ####1 -1 }
587       }{}
588     }
589   }
590 }

```

(End of definition for \\_\_tbl\_gset\_untagged\_row\_cells:nn.)

\\_\_tbl\_if\_tag\_cell:nn

We must be able to detect if a cell should be tagged. For this we define a conditional — if more options are needed it can be extended.

```

591 \prg_new_protected_conditional:Npnn \__tbl_if_tag_cell:nn #1 #2 % #1 row, #2 col
592 { T,TF }
593 {

```

```

594     \prop_get:NeNTF \g__tbl_untagged_cells_prop
595     {\int_eval:n{#1},\int_eval:n{#2}}\l__tbl_tmpa_tl
596     { \prg_return_false:}
597     { \prg_return_true: }
598 }

```

(End of definition for \\_\_tbl\_if\_tag\_cell:nn.)

## 5.6 Misc stuff

\\_\_tbl\_show\_curr\_cell\_data: Show the row/column index and span count for current table cell for debugging.

```

599 \cs_new_protected:Npn \__tbl_show_curr_cell_data: {
600     \__tbl_trace:n { ==>~ current~cell~data:~
601         \int_use:N \g__tbl_row_int ,
602         \int_use:N \g__tbl_col_int ,
603         \g__tbl_span_tl
604     }
605 }

```

(End of definition for \\_\_tbl\_show\_curr\_cell\_data:.)

\\_\_tbl\_add\_missing\_cells: The storing and use of the number of missing cells must happen at different places as the testing happens at the end of the last cell of a row, but still inside that cell, so we use two commands. The one adding is used in the row/end socket.

```

606 \cs_new:Npn \__tbl_add_missing_cells:
607 {

```

The TD-socket messages are issued after the message about the end-row socket, but the structure is ok, so better issue a message for now to avoid confusion:

```

608     \int_compare:nNnT \g__tbl_missing_cells_int > 0
609     {
610         \__tbl_trace:n {==>~
611             ~Inserting~\int_use:N \g__tbl_missing_cells_int \space
612             additional~cell(s)~into~previous~row:}
613         \int_step_inline:nn { \g__tbl_missing_cells_int }
614         {
615             \int_gincr:N \g__tbl_col_int
616             \UseTaggingSocket{tbl/cell/begin}
617             \UseTaggingSocket{tbl/cell/end}
618         }
619     }
620 }

```

(End of definition for \\_\_tbl\_add\_missing\_cells:.)

\g\_\_tbl\_struct\_table\_tl We need to store the structure numbers for the fine tuning in the finalize socket. For now we use a rather simple system: A sequence that hold the numbers for the row structures, and one that holds comma lists for the cells.

\l\_\_tbl\_saved\_struct\_table\_tl \g\_\_tbl\_struct\_table\_tl will hold the structure number of the table, \g\_\_tbl\_struct\_rows\_seq will hold at index i the structure number of row i, \g\_\_tbl\_struct\_cells\_seq will hold at index i a comma list of the cell structure numbers of row i. \l\_\_tbl\_saved\_struct\_rows\_seq \l\_\_tbl\_saved\_struct\_cells\_seq \g\_\_tbl\_struct\_cur\_seq \l\_\_tbl\_saved\_struct\_cur\_seq is used as a temporary store for the cell structures of the current row. We need also local version to store and restore the values.

```

621 \tl_new:N \g__tbl_struct_table_tl

```

```

622 \tl_new:N \l__tbl_saved_struct_table_tl
623 \seq_new:N \g__tbl_struct_rows_seq
624 \seq_new:N \l__tbl_saved_struct_rows_seq
625 \seq_new:N \g__tbl_struct_cells_seq
626 \seq_new:N \l__tbl_saved_struct_cells_seq
627 \seq_new:N \g__tbl_struct_cur_seq
628 \seq_new:N \l__tbl_saved_struct_cur_seq

(End of definition for \g__tbl_struct_table_tl and others.)

```

`\__tbl_init_struct_data:` Save the global structure data variables locally so the we can restore them when the table ends (important in case of nested tables).

This is also the right point to initialize them. `\g__tbl_struct_table_tl` is set elsewhere.

```

629 \cs_new_protected:Npn \__tbl_init_struct_data: {
630   \tl_set_eq:NN \l__tbl_saved_struct_table_tl \g__tbl_struct_table_tl
631   \seq_set_eq:NN \l__tbl_saved_struct_rows_seq \g__tbl_struct_rows_seq
632   \seq_set_eq:NN \l__tbl_saved_struct_cells_seq \g__tbl_struct_cells_seq
633   \seq_set_eq:NN \l__tbl_saved_struct_cur_seq \g__tbl_struct_cur_seq
634   %
635   \seq_gclear:N\g__tbl_struct_rows_seq
636   \seq_gclear:N\g__tbl_struct_cells_seq
637   \seq_gclear:N\g__tbl_struct_cur_seq
638 }

(End of definition for \__tbl_init_struct_data:.)

```

`\__tbl_restore_struct_data:`

```

639 \cs_new_protected:Npn \__tbl_restore_struct_data: {
640   \tl_gset_eq:NN \g__tbl_struct_table_tl \l__tbl_saved_struct_table_tl
641   \seq_gset_eq:NN \g__tbl_struct_rows_seq \l__tbl_saved_struct_rows_seq
642   \seq_gset_eq:NN \g__tbl_struct_cells_seq \l__tbl_saved_struct_cells_seq
643   \seq_gset_eq:NN \g__tbl_struct_cur_seq \l__tbl_saved_struct_cur_seq
644 }

(End of definition for \__tbl_restore_struct_data:.)

```

## 5.7 longtable

`\__tbl_patch_LT@makecaption`

This patch is quite similar to the one for LaTeX's `\@makecaption` we also have to change the parbox sockets.

```

645 \def\__tbl_patch_LT@makecaption#1#2#3{%
646   \LT@mcol\LT@cols c{%
647     % test can go after merge
648     \str_if_exist:cT { l__socket_tagsupport/parbox/before_plug_str }
649     {
650       \AssignTaggingSocketPlug{parbox/before}{noop}
651       \AssignTaggingSocketPlug{parbox/after}{noop}
652     }
653     \hbox to\z@{\hss\parbox[t]\LTcapwidth{%
654       \reset@font
655       \tag_suspend:n{caption}
656       \sbox\@tempboxa{#1{#2:~}#3}%
657       \tag_resume:n{caption}

```

```

658 \ifdim\wd\@tempboxa>\hsize
659 #1{#2:~}#3%
660 \else
661 \hbox to\hsize{\hfil#1{#2:~}#3\hfil}%
662 \fi
663 \endgraf\vskip\baselineskip}%
664 \hss}}

```

*(End of definition for \\_tbl\_patch\\_LT@makecaption.)*

Overwrite the longtable definition. That will probably break somewhere as they are various package which patch too.

```

665 \AddToHook{package/longtable/after}
666 {
667 \cs_set_eq:NN \LT@makecaption\_tbl_patch_LT@makecaption
668 }
669 \</package>
670 \<*latex-lab>
671 \ProvidesFile{table-latex-lab-testphase.ltx}
672 [\ltblabtbldate\space v\ltblabtblversion\space latex-lab wrapper table]
673 \RequirePackage{latex-lab-testphase-table}
674 \</latex-lab>
675 \<*latex-lab-alias>
676 \ProvidesFile{tabular-latex-lab-testphase.ltx}
677 [\ltblabtbldate\space v\ltblabtblversion\space latex-lab wrapper tabular]
678 \RequirePackage{latex-lab-testphase-table}
679 \</latex-lab-alias>

```